

181-00193 Article Number:

Solid Cable and Wiring Duct, 1.5" x 1.5", Non-Adhesive, PVC, White, 30ft/box Description:

Base Data		
	Local Order Number	181-00193
	Туре	SD1.5X1.5
	Color	White (WH)
	Features and Benefits	 A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement. Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)
	Quantity Per	box
	Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.
	Technical Description	Non-Adhesive
	Short Description	Solid Cable and Wiring Duct, 1.5" x 1.5", Non-Adhesive, PVC, White, 30ft/box
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.5"
	Width W (Metric)	38.1mm
	Width W2 (Imperial)	1.5"
	Width W2 (Metric)	38.1mm
	Height H (Imperial)	1.57"
	Height H (Metric)	39.9mm
	Mounting Hole Centers (Imperial)	4.0"

generated on: 4/28/2017

181-00193



Material and Specifications		
	Material	Polyvinylchloride (PVC)
	Material Shortcut	PVC
	Flammability	self-extinguishing
	Operating Temperature	+122°F (+50°C)
	ROHS Compliant	Yes
	Certification/Specification	CSA
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	30.0ft
	Package Quantity (Metric)	9.1m
	Customs Number(Schedule B)	3925900000

generated on: 4/28/2017