

Article Number: 300-73604



Heat Shrink Tubing, 2:1 Shrink Ratio, 3/16", 2.4/1.2 Dia, PO, Black, 1000 ft/reel Description:

Base Data		
	Local Order Number	300-73604
	Туре	TCN20-4.8/2.4
	Color	Black (BK)
	Features and Benefits	<ul> <li>Tubing is 2:1, thin wall and self extinguishing providing good resistance to common fluids and solvents.</li> <li>Low shrink temperature gives excellent physical and electrical performance.</li> <li>Available in multiple diameters and lengths offering several options to fit specific needs.</li> </ul>
	Quantity Per	box
	Product Description	TCN20 Heat Shrink is a general purpose, thin wall tubing used to protect electrical and mechanical wiring. Polyolefin material is self extinguishing and resistant against common fluids and solvents. The low shrink temperature and mechanical strength make this tubing widely used in the electric and electronics industry. Available in a wide range of diameters up to 2.0" (50.8mm) and multiple lengths. TCN20 Heat Shrink is UL224 125 °C 600V VW-1 and RoHS.
	Short Description	Heat Shrink Tubing, 2:1 Shrink Ratio, 3/16", 2.4/1.2 Dia, PO, Black, 1000 ft/reel
Product Dimensions		
	Length L (Imperial)	1000.0ft
	Length L (Metric)	304.8m
	Printable (Yes/No)	Yes
	Shrink Ratio	2:1
	Trade Size	3/16 "
	Variant	Thin-Wall
	Volume Resistance (Ohm cm)	10 <sup>14</sup> Ω cm
	Nominal Diameter (Imperial)	3/16"
	Nominal Diameter (Metric)	4.8mm
	Wall Thickness WT (Metric)	0.50mm
	Recovered Diameter d (metric)	2.4mm
	Recovered Diameter d (imperial)	0.094"

generated on: 4/28/2017

## 300-73604



Product Dimensions Supplied Diameter D Supplied Diameter D		0.189" 4.8mm
Supplied Diameter D	(metric)	4.8mm
Material and		
Material and		
Specifications		
Material		Polyolefin, cross-linked (PO-X)
Material Shortcut		PO-X
Dielectric Strength (M	etric)	20 kV/mm according to IEC 243
Elongation at break		400%
Flammability		self-extinguishing
Halogenfree		No
Shrink Temperature		+212 °F (+100 °C)
Operating Temperatu	re	-67°F to +257°F (-55°C to +125°C)
ROHS Compliant		Yes
Certification/Specifica	tion	UL224 125 °C 600V VW-1
UL Recognized (US)		Yes
Logistic and		
Packaging		
Package Quantity (Im	perial)	1000ft
Package Quantity (Mo	etric)	304.8m
Customs Number(Sch	nedule B)	3926909987

generated on: 4/28/2017