

# Innovative **Technology** for a **Connected** World

## **Omni-directional Panel Antenna**



### **DUAL BAND 802.11 a/b/g/n SPATIAL DIVERSITY ANTENNA**

Laird Technologies' S24493D antenna offers the system integrator a spatial diversity antenna system that will accommodate all applications and modes in both the 2.4-2.5 GHz and 5.15-5.875 GHz bands. This one diminutive aesthetically neutral package covers every single-band and multi-band multi-mode application that you might be confronted with in the field.

The design also provides flexibility for future changes in deployed system modes. In place of spatial diversity, each port can be used individually to support 802.11b/g and 802.11a systems simultaneously for dual-band non-diversity deployments.

The radiation patterns are uniform and symmetrical, providing high levels of signal density into defined coverage zones. This is critical for high data rate, high-capacity configurations. Mounting options allow either flush surface ceiling mount with supplied ceiling clips (\$24493DS) or mast mount (\$24493DM) with pole mounting hardware.

### FEATURES RoHS

- 802.11 a/b/g/n and wide band frequency coverage
- Variety of cable lengths and connectors available
- Fast and easy installation with either ceiling clips / mast mount
- Neutral color and diminutive profile disappears into the environment

#### **MARKETS**

- Hospital
- Campus
- Research Institute
- Public safety wireless systems
- Transport Terminals

PARAMETER	SPECIFICATION
Antenna Part Number	S24493DS / S24493DM
Frequency Range (GHz)	2.4 - 2.5 & 4.90 - 5.99 GHz
Gain (dBi) w/36" cable	(3) @ 2.5 / (4) @ 5.5 GHz
3 dB Beamwidth - Elevation	60° @ 2.5 / 58° @ 5.5 GHz
3 dB Beamwidth - Azimuth	Omnidirectional
Polarization	Linear Vertical
VSWR	2.0:1
Pigtail (in)	36
RF connector	Reverse TNC / type N (m)
Power Rating (watts)	2
Dimensions in. (mm)	6.16x3.66x.89 (156x93x22)
Weight (kg)	.23 kg
Operational Temperature (C°)	0° to +55°
Mount style	Ceiling tile / mast

### global solutions: local support ...

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-S24493D 0509

Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be lailed for incidental or consequental damages of any list in All Laird Technologies products are sold pursuant to the Laird Technologies terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request. All Laird Technologies for products are sold pursuant to the Laird Technologies' terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request.